

# Installation Instructions

2.0 Amps MAX @ 12V

## 8891023 & 8891026 LED Dashboard Mount Strobe Lights

Tilt Adjustment . Screws



Suction Cups

Power On/Of

Flash Pattern Selector

#### Installation

Choose windshield location.

Clean windshield with alcohol.

Loosen screw on each side (2 screws total) and adjust tilt to match angle of windshield. Once correct angle is found, secure screws.

Attach light using supplied suction cups to windshield.

#### **Operation**

Insert power plug into vehicle accessory power port. Push power on/off switch. Push flash pattern selector switch for next pattern.



FP#	Flash Patterns
1	Single
2	Double
3	Quad
4	Double
5	Random
6	Single (Split)
7	Double (Split 1)
8	Quad (Split 1)
9	Quint (Split)
10	Double (Split 2)
11	Burst - (Split 1)
12	Quad - (Split 2)
13	Burst - (Split 2)
14	Quad - (All)
15	Quint - (All)
16	Burst - (All)
17	Half Steady - 1
18	Half Steady - 2
19	OFF

### **WARNING**

Do not look directly into LEDs while in operation; this may cause momentary blindness and/or eye damage.

Warranty

Buyers Products Company warranties all LED Strobe and LED Work Light products to the original owner against defects in workmanship and material for a period of one (1) years from the date of purchase unless otherwise specified. Buyers Products must review each warranty claim and reserves the right to offer a refund for the original sale price of the product or replace the defective light. The one (1) year warranty is non transferable, applies to the original owner, and is subject to the following terms and conditions. The warranty will be void in cases of misuse, severe abuse, and failure to properly install the LED Light. Breakage of the lens or housing, corrosion at the plug, wire wicking, voltage spikes, and product failure caused by road chemicals and acid type washes are not warrantable claims. This warranty gives you specific legal rights and you may also have other legal rights that vary from state to state.